



## United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	F	LING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO	CONFIRMATION NO.
10/007,468	07,468 11/07/2001		Shinichi Shimomaki	01727/LH	2858
1933	7590	06/20/2006		EX	AMINER
FRISHAU	F, HOLTZ	Z, GOODMAN &	SHAP	SHAPIRO, LEONID	
220 Fifth Av	venue .				<del></del>
16TH Floor			ART UNIT	PAPER NUMBER	
NEW YORK	K, NY 10	0001-7708		2629	

DATE MAILED: 06/20/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

-		Application No.	Applicant(s)				
		10/007,468	SHIMOMAKI, SHINICHI				
	Office Action Summary	Examiner	Art Unit				
		Leonid Shapiro	2629				
	The MAILING DATE of this communication a						
Period for	, ,						
WHICH - Extens after S - If NO p - Failure Any re	PRTENED STATUTORY PERIOD FOR REIDEVER IS LONGER, FROM THE MAILING allows of time may be available under the provisions of 37 CFR IX (6) MONTHS from the mailing date of this communication. Deriod for reply is specified above, the maximum statutory perion to reply within the set or extended period for reply will, by staply received by the Office later than three months after the mail patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICAT 1.136(a). In no event, however, may a reply bod will apply and will expire SIX (6) MONTHS to the cause the application to become ABANDO	ION.  e timely filed  from the mailing date of this communication.  DNED (35 U.S.C. § 133).				
Status							
2a) ☐ 3 3) ☐ 3	Responsive to communication(s) filed on $\underline{22}$ . This action is <b>FINAL</b> . 2b) $\boxtimes$ This action is application is in condition for allow closed in accordance with the practice under the	his action is non-final. vance except for formal matters,	•				
		1 Ex parte Quayle, 1999 O.B. 11	, 433 0.0. 213.				
Disposition of Claims							
5)□ ( 6)⊠ ( 7)□ (	Claim(s) <u>1-3,5-12 and 14-19</u> is/are pending a) Of the above claim(s) is/are without Claim(s) is/are allowed. Claim(s) <u>1-3,5-12,14-19</u> is/are rejected. Claim(s) is/are objected to. Claim(s) are subject to restriction and	rawn from consideration.					
Application	on Papers						
	he specification is objected to by the Exam	iner					
10) ☐ The drawing(s) filed on is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.							
=	Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
F	Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).						
11) 🗌 T	11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority ur	nder 35 U.S.C. § 119						
a) [	acknowledgment is made of a claim for foreignal.  All b) Some * c) None of:  Certified copies of the priority docume  Copies of the certified copies of the papplication from the International Burden the attached detailed Office action for a least	ents have been received. ents have been received in Applic riority documents have been rece eau (PCT Rule 17.2(a)).	cation No eived in this National Stage				
Attachment(	c)						
_ / '	of References Cited (PTO-892)	4) 🔲 Interview Summ	nary (PTO-413)				
2) Notice 3) Informa	of Draftsperson's Patent Drawing Review (PTO-948) ation Disclosure Statement(s) (PTO-1449 or PTO/SB/N No(s)/Mail Date	Paper No(s)/Ma					

Application/Control Number: 10/007,468

Art Unit: 2629

## Claim Rejections - 35 USC § 103

The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

1. Claims 1-3, 5-9 and 11-12, 14-18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lee et al, USPN 5,510,807, in view of Moon, USPN 5,825,343 and Jenkins et al. USPN 5,561,381.

Claims 1 and 12. Lee et al. teaches a liquid crystal display device comprising a liquid crystal display panel [14] having a plurality of signal lines [column lines 24], a plurality of scanning lines, [26] and a plurality of display pixels [19] arrayed in a matrix and provided respectively near cross-points between the signal lines and the scanning lines through switching elements [20]. A driver supplies the plurality of signal lines [through column driver 16] with a display signal in a field period, and which scans [through row select driver 25] the plurality of scanning lines, to apply the display signal to the plurality of display pixels. Lee, col. 1, lines 20 – 55; col. 3, lines 13 – 40; and figure 1.

Lee teaches that the driver include means which supplies an initialization signal [precharge voltage V+ or V- during 6μs precharge time] including a constant single pulse voltage to the plurality of signal lines [(i) or (j)], thereby applying the initialization signal to the display pixel, and thereafter supplies the display signal [(0~5V) or ((-5~0V) video signal during the video data banks periods #1 - #6] to the signal line and after completing the supply of initialization (precharge) signal to the plurality of signal lines and completion of the supply of the first gate pulse to the plurality of scanning lines and after a predetermined hold time (first positive pulse and first negative pulse on lines (f), (g), (h) of Figure 4) supplying the display

Art Unit: 2629

signal to the display pixel, at least one signal application period set within the field period. Lee, col. 5, line 62 – col. 6, line 33; col. 6, line 63 – col. 7, line 4; col. 7, lines 59 – 64; and figure 4.

Lee teaches the liquid crystal display panel includes a plurality of pixel electrodes arrayed in a matrix through the switching elements, common electrodes opposed to the-pixel electrodes, and liquid crystal sandwiched between the-pixel electrodes and the common electrode. Lee, col. 1, lines 20 - 55; col. 3, lines 13 - 40; and figure 1.

Lee teaches that the scanning line [select scan line, N (k)] is one during both the precharge and the display signal time. Lee, col. 5, line 62 – col. 6, line 4; and figure 4. Thus, Lee does not teach a first gate pulse, a second gate pulse and the hold.

Moon teaches a first gate pulse and a second gate pulse [two-pulse gate electrode voltage signals to each gate line]. Moon, col. 3, lines 46 - 55; col. 4, lines 50 - 58; col. 5, lines 21 - 25; and figures 5, and 7 - 9.

As shown in FIG. 8, the gate electrode voltage pulse is twice applied to the gate lines of the liquid crystal pixels. The first gate electrode driving pulse precharges the liquid crystal capacitor  $C_{lc}$  and the grey voltage, which is applied to source terminal of the TFT-LCD is applied to the liquid crystal capacitor  $C_{lc}$  by the second driving pulse.

Moon, col. 4, lines 52 - 58.

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the first and second gate pulse as taught by Moon with the liquid crystal display device as taught by Lee to improve a clear picture by double the duration of the driving voltage. Moon invites such combination by teaching,

As described above, the present invention provides a driving device and a driving method for a TFT-LCD in which the liquid crystal pixels are correctly driven by applying a two-pulse gate electrode voltage which have the effect of doubling the duration of the driving pulse.

Application/Control Number: 10/007,468

Art Unit: 2629

Moon, col. 5, lines 21 0 25. See also Moon, col. 1, lines 7 - 14; and col. 2, lines 24 - 58.

Lee et al. and Moon do not disclose the hold time is set to a time longer than a voltagewrite response time of the liquid crystal in the display pixels.

Jenkins et al. teaches the hold time is set to a time longer than a voltage-write response time of the liquid crystal in the display pixels. (See Fig. 5, items T4,T8, Col. 7, Lines 35-40).

It would have been obvious to one of ordinary skill in the art at the time of the invention to incorporate Jenkins teachings into Moon and Lee et al. system in order to reliable charge the cell capacitance (See Col. 2, Lines 1-4).

Claim 2. Jenkins et al. teaches LCD panel is a non-auxiliary capacitance type (See Fig. 1, items 112,120, Col. 3, Lines 28-40).

Claim 3. Lee teaches that each of the switching elements of the liquid crystal display panel includes a thin film transistor. Lee, col. 1, lines 29 - 31.

Claims 5 and 14. Lee teaches that the initialization signal voltage in the driver has a value equal to or higher than a maximum voltage value of the display signal. Lee, col. 6, lines 54-62.

Claims 6 and 15. Lee teaches that the driver applies the initialization signal voltage and the display signal to the display pixels connected to the scanning lines of the liquid crystal display panel, at a predetermined time interval, sequentially for every one of the scanning lines, in the signal application period in the field period, and the time interval is set to a value at which timings of applying the initialization signal voltage and the display signal to every of the display pixels connected to each of the scanning lines do not overlap each other. Lee, col. 1, lines 20 – 56; col. 3, lines 14 – 39.

Application/Control Number: 10/007,468

Art Unit: 2629

Claims 7 and 16. Lee teaches that the application timing is set such that the driver applies the initialization signal voltage simultaneously to all the display pixels of the liquid crystal display panel, and thereafter applies the display signal to the display pixels connected to the scanning lines of the liquid crystal display panel, at a predetermined time interval, sequentially for every one of the scanning lines, in the signal application period in the field period. Lee, col. 5, line 62 – col. 6, line 33; and figure 4.

Claims 8, 9, 11, 17 and 18. Lee teaches that the display signal comprises first, second, and third color component signals, and the driver applies the initialization signal voltage and thereafter applies any one of the first, second, and third color component signals, to the display pixels connected to the scanning lines of the liquid crystal display panel, sequentially for every one of the scanning lines, in each of the signal application periods of the field period. Lee, col. 3, lines 40 - 53.

2. Claims 10 and 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lee et al, in view of Moon, Jenkins et al. as applied to claims 9 or 18 above, and further in view of Taira et al, USPN 6,825,823 B1.

Claims 10 and 19.

Neither Lee nor Moon, Jenkins et al. specifically teach controlling the light emission color or the illumination light source.

Taira teaches controlling light emission color of an illumination light source, wherein the controlling of the light emission color includes controlling the light emission color of the light source so as to correspond to any of the first, second, and third color component signals that is

applied to the display pixels in the applying of the display signal. Taira, col. 1, lines 6 - 11; and col. 2, lines 42 - 64.

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the color scheme as taught by Taira with the liquid crystal display device and method as taught by Lee and Moon, Jenkins et al. to provide sufficient response time to reduce color breakup interference. See Taira, col. 2, lines 28 – 41.

## Response to Arguments

3. Applicant's arguments with respect to claim1-3,5-12,14-19 have been considered but are most in view of the new ground(s) of rejection.

## Telephone Inquire

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Leonid Shapiro whose telephone number is 571-272-7683. The examiner can normally be reached on 8 a.m. to 5 p.m..

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Richard Hjerpe can be reached on 571-272-7691. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/007,468 Page 7

Art Unit: 2629

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

LS 06.11.06

> KICHARD HJERPE SUPERVISORY PATENT EXAMINER TECHNOLOGY CENTER 2600